



THE MORALE BUILDER

Live Pure!



Point of Use Morale Builder Water Cooler AB Specifications

Model	Morale Builder
Cold Water	1.4 GAL of 50°F/hr (5.5ℓ of 10°C)
Hot Water	1.8 GAL of 185°F/hr (7ℓ of 85°C)
Room Temp. Water	Non
Dimensions	11.4" W (290 mm) 14.4" D (365 mm) 44.9" H (1140 mm)
Shipping Weight	55 lbs (25 kg)

*Specifications are subject to change without notice.

Performance Benefits

SAFETY

The Morale Builder utilizes a dual magnetic float for redundancy and assurance, Morale Builder can minimize the risk of water leakage in connecting parts of the system.

HYGIENE

Rather than a plastic tank, the Morale Builder has a hygienic stainless steel tank.

CONVENIENCE

The Morale Builder's dispensing position is 5" higher than bottled water dispensers.

SCALD FREE

The Morale Builder's child safety faucet comes standard and get rid of (both cup push and press type available)

HIGH CAPACITY FILTRATION

Available with Reverse osmosis or multimedia spring water filtration. Preventative filter changes included.

HIGH CAPACITY TANK

The 9 liter storage tank is capable of supplying large offices of up to 20 people.

General Specification

CABINET

Top and front panels made of molded ABS plastic and side panels made of electrically zinc-coated steel with high polymer polyester resin.

COLD WATER THERMOSTAT

Ice cold water delivered by an adjustable thermostat.

FAUCETS

Durable, self-closing, and easy to operate.

DRIP RECEPTACLE

Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid diverts drip water into receptacle.

HOT WATER

185°F water on demand for teas and soup.

HOT WATER TANK

Hygienic type stainless steel. Highly efficient internal heating element. Fire proof insulation.

REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector.

Pure Water Systems Inc.
245 Vine St, Reno, NV 89503
office@renowaterfilters.com
www.renowaterfilters.com

775-324-2001

NV Lic. # 49317A
CA. Lic # 1054103