



INNOVATION MAKES MASTERPIECE



PERFORMANCE BENEFITS

SAFETY

By eliminating water pressure in magnetic dual float valve for the remaining filtration system, D16 can minimize the risk of water leakage in connecting parts of the system.

HYGIENE

Rather than using a plastic tank, D16 has an hygienic stainless steel tank, minimizing expensive frequent visit for cleaning.

CONVENIENCE

By lifting up the height of unit, D16 has higher dispensing position by 5 inches than bottled water dispensers.

CLOVER MADE

A quality product maker, Clover designs and manufactures with craftsmanship.

SCOLD FREE

D16 has children safety faucet as standard. (Both cup push and press type available)

BIGGER SIZE FILTER SPACE

D16 has enough space to accommodate up to 5 filters and booster pump, so that it can meet various range of customers needs.

BIGGER SIZE TANK

9 liters storage tanks can meet large consumption at once such as in large offices, schools and hospitals.



GENERAL SPECIFICATION

CABINET

Top and front panels are molded of ABS plastic and side panels are made of electric zincoated steel with high polymer polyester resin.

COLD WATER THERMOSTAT

Temperature is controlled to 4°C~ 10°C by adjustable thermostat, easily accessible on back.

FAUCETS

Durable polypropylene.
Self closing type. Easy to operate.

DRIP RECEPTACLE

Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid diverts drip water into receptacle.

HOT WATER

(Model D16A) Water Temperature is controlled to nearly 185°F (85°C) by automatic, On-off lamp switch is easily accessible on the rear control panel.

HOT WATER TANK

Hygienic type stainless steel. Highly efficient internal heating element. Fire proof insulation.

WARRANTY

One year on the sealed refrigeration system and most component parts.

REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube.

Point of Use Water Cooler D16 A/B Specifications

MODEL	D16A	D16B
COLD WATER	1.4 GAL of 50°F/hr (5.5ℓ of 10°C)	
HOT WATER	1.8 GAL of 185°F/hr (7ℓ of 85°C)	NON
ROOM TEMP.WATER	NON	O
DIMENSIONS	11.4" W (290mm) 14.4" D (365mm) 44.9" H (1140mm)	
SHIPPING WEIGHT	55 lbs (25Kg)	51 lbs (23Kg)

※ Specifications are subject to change without notice.



Kevin Hunter
National Sales Manager
303-333-8250 x107
Kevin.Hunter@osiml.com